

MAY 28, 2001 1999P03326WO PCT/DE00/01343

· 4 -

DE 000001343

What is claimed is?
Patent Claims

Compassing &

An insulation displacement \contact, (for example siotted, has (Aa which terminal strips, for contact-making a 5 region region bracket L(1), (which contact surrounded and reinforced by an outer spring clip ((3), the spring clip ((3) is designed characterized in that blade insulation displacement least one end region, with the cutting blade (4) on the region or regions forming an entry region which is

capable of cutting and [is] located in front of the contact region.

2. (A The insulation displacement contact as claimed in claim 1, characterized in that the contact-making slot (2) is designed with blunt contact zones in order to protect a conductor core.

3. (An The insulation displacement contact as claimed in claim 2, Characterized in that the spring clip (3) and

cutting blades (4) are formed from suitably hard material, and in that the contact region (6) is formed from electrically highly conductive material.

4. The insulation displacement contact as claimed in one of the preceding claims, characterized in that seach connecting bracket (1) forms a contact-making slot (2) at each of its ends.

in One of the preceding claims, Characterized in that the spring clip (3) and or the connecting bracket (1)

30 are designed such that the limbs of the spring clip (1) secure the contact-making slot (2) in its position.

6. (An insulating displacement contact as claimed in one of the preceding claims, characterized in that the

surround removed the contact